

ORATORIO

The musical form of the ORATORIO combines the full force of human and orchestral voices. Giving this name to our most capable center channel speaker acknowledges that film soundtracks require the center channel speaker not only to provide dialogue reproduction, but also to be an equal partner with the front speakers in reproducing the full force of the dynamic and tonal structure of the main stage. As the perfect partner to a large-scale MAHLER or STRAUSS based theater, ORATORIO shares technical features developed for both of those benchmark products. Housed within the striking cabinet, raked back for perfect time alignment, sheathed in veneer formed perfectly over the complex corners of its surface, are drivers of extraordinary capability. The silk dome tweeter incorporates a unique multiple magnet system and an integral decoupling mounting block to reduce extraneous resonance interaction. The tweeter block's small size permits placement immediately above the midrange driver for improved dispersion characteristics. Supported by the dual woofers functioning as ultra-low-frequency drivers, the single midrange driver reproduces the entire vocal range, resulting in system voicing of superior clarity and grand scale.

The tradition of unrivaled finish quality continues with the ORATORIO, providing the warmth and beauty of real wood for the most harmonious integration into any listening room. Three finishes are available, each benefiting from Vienna Acoustics' proprietary veneer wrapping technique: a dramatically grained handselected rosewood; a warm and rich handselected beech; and a special high gloss black, featuring an eleven-layer lacquer finish on the front and back baffles, combined with handselected black ash veneer for the main body.

ORATORIO further adds to Vienna Acoustics' heritage of superb physical design and construction, and will ably occupy a place in any ultra high-end Vienna Acoustics home theater system.

Technical Data:

System Type	3 way system
Bass System	Bassreflex
Frequency Response	30 - 30.000 Hz
Bass drivers	2 x VA 9" driver carbon fiber filled, air-dried paper cone
Midrange driver	7" driver carbon fiber filled, air-dried paper cone
Tweeter driver	VA 1" handcoated silicone-layered silk dome 3-Neodymium-magnet construction, center-drilled with damped chamber Massive anti-resonance decoupling
Sensitivity	91 dB
Impedance	4 Ohms
Recommended Power	50 - 300 Watts
Weight per Speaker	60 Ibs / 27 kg
Dimensions (WxHxD)	29.5 x 9,2 x 14,2 inches 750 x 235 x 360 mm

